



TEN PLUS MODEL D2403 - EXTRUDED ALUMINUM LOUVER. ALL PROFILES TO BE 1.6 mm (0.062") 6063-T5 ALUMINUM ALLOY. UNLESS OTHERWISE SPECIFIED, ALL STRUCTURAL ELEMENTS TO BE DESIGNED FOR A LIVE LOAD OF 0.95 kPa (20 Lbs. PER SQ FOOT).

- ☐ THREE COAT 70% PVDF RESIN TO AAMA 2605 STD.
☐ TWO COAT 70% PVDF RESIN TO AAMA 2605 STD.
☐ ONE COAT THERMOSETTING RESIN TO AAMA 2603 STD.
☐ COLOR ANODIC
☐ COLOR: _____
☐ CLEAR ANODIZED ☐ CLASS I ☐ CLASS II
☐ OTHER: _____

- ☐ 16 mm (5/8") EXPANDED ALUMINUM MESH
☐ 12 mm (1/2") WELDED & REGALVANIZED STEEL MESH
☐ 12 mm (1/2") INTER-CRIMPED ALUMINUM WIRE
☐ 18 X 18 ALUMINUM MESH INSECT SCREEN
☐ OTHER:

- ☐ SILL FLASHING REQUIRED
- ☐ LOUVER SETBACK DIM. _____
- ☐ GLAZING FRAME OPTION
- ☐ FLANGE FRAME OPTION _____
- ☐ _____

NOTE: SOME OPTIONS MAY LEAD TO EXTRA COSTS TO THE CONTRACT. ENQUIRE WITH YOUR REP.



PROJECT:

SPEC. SECTION:

CUSTOMER:

ARCHITECT:

TEN PLUS CONTACT:

DRAWN BY:

SCALE:
AS NOTED


CHECKED
BY:

DRAWING:

MODEL 2403 DRAINABLE BLADE
LOUVER

JOB No.

DWG No.



NOTES:



☐ SILL FLASHING REQUIRED

☐ LOUVER SETBACK DIM. _____

☐ GLAZING FRAME OPTION

☐ FLANGE FRAME OPTION

☐ _____

☐ _____

	revisions:	
	issued for client review	2023-00-00



TENPLUS
ARCHITECTURAL PRODUCTS LTD.

5-2333 MILLRACE COURT
MISSISSAUGA, ON L5N 1W2
TEL: 905-363-2306
FAX: 905-363-2309
WWW.TENPLUS-ONLINE.COM

PROJECT:

SPEC. SECTION:

CUSTOMER:

ARCHITECT:

TEN PLUS CONTACT:

DRAWN BY:

SCALE:
AS NOTED

CHECKED
BY:

DRAWING:
MODEL 2403 DRAINABLE BLADE
LOUVER

JOB No.

DWG No.